

Erica Synths – Sample Drum

- [Manual PDF](#)

[Erica Synths Sample Drum Manual \(PDF\)](#)

Erica Synths Sample Drum Cheat Sheet

Overview

Dual-channel, performance-focused sample player. Each channel is independently addressable and features: - Fast sample playback and triggering - Live and auto/manual slicing - Extensive CV assignment - FX and envelopes per channel - Sample recording and trimming - Project memory

Front Panel Controls & Features

| Control/Jack | Description |
|--------------------|--|
| A/DATA | Main data/selection encoder (push to confirm/select) |
| B, C, D/BACK, E, F | Context-sensitive encoders (see menus/functions below). D/BACK: also acts as a back/return button. |
| TRG1/PLAY | Manual Trigger button Ch1 (Performance mode only); preview sample |

| Control/ Jack | Description |
|---------------------------|---|
| TRG2/ SHIFT | Manual Trigger button Ch2; also SHIFT for accessing secondary functions; preview waveform/sample info |
| OLED Screen | Visual feedback, waveforms, menus, scopes |
| **SD Card Slot | For sample/projects management (microSD, must keep directory structure as specified) |
| CH1/CH2 Toggle | Select which channel (for sample loading/editing/assign) |

Input/Output Jack Summary

| I/O | Function | Voltage Range |
|-------------------------------|---|---|
| TRIG 1, 2 | Trigger Inputs (Ch1 & Ch2 sample playback) | |
| CV1, CV2, CV3 (x2) | 3 Assignable CV per Channel: tune/sample/start/end/loop/slice FX/env, etc. CV3 on CH2 used for sample recording | Configurable: -5V to +5V -10V to +10V 0V to +5V 0V to +10V 1V/Oct (no depth setting) |
| OUT 1, 2 | Individual Channel Audio Outputs | 10V ptp max (settable via menu) |
| SD | MicroSD slot for samples/projects | |
| Power | | |

| I/O | Function | Voltage Range |
|-----|---|---------------|
| | Standard Eurorack header (65mA @ +12V, 2mA @ -12V) | |

Top-Level Workflow

1. Loading Samples

- Prepare mono 16-bit, 48kHz (or lower) WAVs, store in `SAMPLES` folder on SD card.
- In `LIBRARY` Menu, select samples with A/DATA encoder; push to upload to RAM.
- Preview with `TRG1/PLAY` (audio), `TRG2/SHIFT` (waveform/size).

2. Sample Editing (`SAMPLE` Menu)

- Access playback start, loop, end; play direction/mode (forward, backward, looping).
- Assign tuning (supports proper 1V/Oct).
- Enter slicing (auto: linear/zero-cross; or manual with ADD/ REMOVE slices).
- Slices: up to 32 per sample; playback modes: FWD, BKW, RND, CV, NONE.
- Adjust envelope: attack, hold, decay (time & shape); Short/Mid/ Long/Relative scaling.

3. Recording Samples

- In `LIBRARY` menu, select `RECORD` for sample input via `CV3 (CH2)`.
- Set input `RANGE`, `LEVEL`, and `THRESHOLD`.
- 48kHz, 12-bit ADC, 30 sec max.
- Trim edit, slice and save to SD.

4. CV Assignment

- Assign any CV input on each channel to nearly any parameter (tune, playback mode, start, end, envelope stages/shape, FX params, slice, etc.).
- Set CV input range:
 - -5V/+5V (default, most LFOs)
 - -10V/+10V
 - 0/+5V (for sequenced sources)
 - 0/+10V (envelopes)
 - 1V/Oct (for pitch/slice/sample)
- Assign depth for mod destinations. View incoming signals on scope.

5. FX

- Delay, Reverb, Lowpass/Highpass, Bitcrush, Fold, Drive (per channel).
- 3 parameters each, CV-assignable.

6. Performance Menu

- Assign 6 main encoders (A–F) to instantly tweak any assignable parameter per channel.
- Encoders: A/B/C for Ch1, D/E/F for Ch2.

7. Projects & Settings

- Save all settings (samples, edits, FX, CV, encoder assignments) as Projects (Single: one channel, Double: both).
- Recall instantly for performance. Double loads interrupt playback.
- Update system, adjust output levels, display settings, and trigger delays in SETTINGS.

Quick Reference

KNOBS/ENCODERS

- **A/DATA:** select, confirm, menu navigate (push to enter).
- **B/C/D/E/F:** context: start/loop/end/slice/fx/env/assign CV parameters, etc.
- **D/BACK:** "return/back" to previous screen.

BUTTONS

- **TRG1/PLAY:** Manual trig Ch1.
- **TRG2/SHIFT:** Manual trig Ch2 or SHIFT (hold).
- **CH1/CH2 Toggle Switch:** Select channel for edit/load/assign.

INPUT JACKS

- **CH1:** TRIG1, CV1, CV2, CV3
- **CH2:** TRIG2, CV1, CV2, CV3 (CV3 = REC input)

OUTPUT JACKS

- **OUT1:** Audio out ch1
- **OUT2:** Audio out ch2

Technical Specs

- **Sample Playback:** ~5 min mono RAM per load
- **Sample Rate:** 48kHz, 16bit (ADC record: 48kHz, 12bit)
- **Pitch:** 1V/Oct accurate (C0–C8 range)
- **Panel:** 14HP, 30mm depth
- **Power:** 65mA @ +12V, 2mA @ -12V

Generated With Eurorack Processor
